

WHAT IS CLAIMED IS:

- sub 93 1. An electro-optical apparatus, comprising:
a pair of substrates, the pair of substrates having an outer surface;
an electro-optical element sandwiched between the pair of substrates;
5 and
an antistatic layer provided on the outer surface of at least one of the
pair of substrates.
2. The electro-optical apparatus according to claim 1, the antistatic layer
being formed of an inorganic material.
- sub 94 10 3. The electro-optical apparatus according to claim 2, the antistatic layer
being formed of silica and conductive particulates.
4. The electro-optical apparatus according to claim 3, the antistatic layer
having a resistance value ranging from 10^6 to $10^9 \Omega/\square$.
- 15 5. A projector comprising the electro-optical apparatus according to
claim 1.
6. A projector, comprising:
a light source;
a color separating optical system that separates a light beam emitted
from the light source into a plurality of colors;
20 a plurality of electro-optical apparatuses that modulate the color beams
that have been separated by the color separating optical system, the plurality of
electro-optical apparatuses including the electro-optical apparatus according to
claim 1;
a prism that synthesizes the color beams that have been modulated by
25 these electro-optical apparatuses; and
a projection lens that projects light emitted from the prism.
7. The projector according to claim 6, further comprising a synthetic resin
component, the synthetic resin component being provided with antistatic treatment.
8. The projector according to claim 7, the synthetic resin component
30 being a holding frame that holds the electro-optical apparatus.
- sub 95 9. A projector, comprising:
a light source;

09891406-062701

an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;

a projection lens that projects a light beam emitted from the electro-optical apparatus; and

5 a field lens disposed adjacent to a light source side of the electro-optical apparatus, at least one surface of the field lens being provided with at least one of an antistatic layer and an antistatic treatment.

10. A projector, comprising:

a light source;

10 an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;

a projection lens that projects a light beam emitted from the electro-optical apparatus; and

15 an incident polarizer disposed adjacent to a light source side of the electro-optical apparatus, at least one surface of the incident polarizer being provided with at least one of an antistatic layer and an antistatic treatment.

11. A projector, comprising:

a light source;

20 an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;

a projection lens that projects a light beam emitted from the electro-optical apparatus;

25 a light transmitting substrate, at least one surface of the light transmitting substrate being provided with at least one of an antistatic layer and an antistatic treatment; and

an incident polarizer disposed adjacent to a light source side of the electro-optical apparatus, the incident polarizer being bonded to the light transmitting substrate.

12. A projector, comprising:

30 a light source;

an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;

a projection lens that projects a light beam emitted from the electro-optical apparatus; and

09891406-062701
10/22/90-90476860

cont.

- 5 13. A projector, comprising:
a light source;
an electro-optical apparatus that forms an optical image from a light
beam emitted from the light source;
a projection lens that projects a light beam emitted from the
electro-optical apparatus;
10 a light transmitting substrate, at least one surface of the light
transmitting substrate being provided with at least one of an antistatic layer and an
antistatic treatment; and
an emergent polarizer disposed adjacent to a projection lens side of the
electro-optical apparatus, the emergent polarizer being bonded to the light transmitting
15 substrate.
14. A projector, comprising:
a light source;
an electro-optical apparatus that forms an optical image from a light
beam emitted from the light source;
20 a projection lens that projects a light beam emitted from the
electro-optical apparatus; and
a phase plate disposed adjacent to at least one of a light source side and
a projection lens side of the electro-optical apparatus, at least one surface of the phase
plate being provided with at least one of an antistatic layer and an antistatic treatment.
- 25 15. A projector, comprising:
a light source;
an electro-optical apparatus that forms an optical image from a light
beam emitted from the light source;
a projection lens that projects a light beam emitted from the
30 electro-optical apparatus;
a light transmitting substrate, at least one surface of the light
transmitting substrate being provided with at least one of an antistatic layer and an
antistatic treatment; and

16. A projector, comprising:
a light source;
an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;
a projection lens that projects a light beam emitted from the electro-optical apparatus; and

17. A projector, comprising:

- a light source;
- an electro-optical apparatus that forms an optical image from a light beam emitted from the light source;
- a projection lens that projects a light beam emitted from the electro-optical apparatus;

18. A projector, comprising:
a plurality of electro-optical apparatuses that modulate a plurality of color beams;
a prism that synthesizes the color beams that have been modulated by the electro-optical apparatuses, the prism having a light incident end surface provided with at least one of an antistatic layer and an antistatic treatment; and
a projection lens that projects the light emitted from the prism.